



DATA SHEET

COLORTONE DECK PROTECTOR

Colortone Deck Protector is an exterior solvent based lead free deck coating protecting your hardwood decks from the harsh ultra violet rays and at the same time with standing the traffic over it. Colortone Deck Protector is available in teak, mahogany and dark oak.

AS APPLICATION IS OUT OF OUR CONTROL COLORTONE PAINTS CC CANNOT ACCEPT LIABILITY FOR ANY LOSS OR DAMAGE

COLORTONE PAINTS CC
P.O BOX 2176
CLAREINCH
7740
TEL 021 703 1553
FAX 021 7031567

APPLICATION

- Ensure that all surfaces are dry, free from dirt and oil
- Remove all existing coatings from the deck by sanding down the deck with a conventional sander
- Brush off dust and wash down deck and allow to dry
- Apply three undiluted coats of Colortone Deck Protector
- Under ideal conditions ie 25 degrees celcius your drying time is 24/48 hours
- Under cold/shaded and wet conditions drying time will be longer
- Ensure that your deck is sealed all round
- Coverage is approximately 10 -12 square meters per litre
- Brushes and rollers are cleaned with mineral turpentine

HEALTH AND SAFETY

- Colortone Deck Protector is flammable and should be stored in a cool dry area
- Keep out of reach of children
- If ingested consult your doctor