

DATA SHEET: COLORTONE DECK PROTECTOR

Product: DECK PROTECTOR (Exterior)

Colours: Clear, Teak, Mahogany, and Dark Oak

Available sizes: 1lt, 5lt and 25 litres

Finish: Matt finish

Description:

Colortone Deck Protector is a lead-free, solvent-based, UV protective, and water repellent exterior, wood deck coating. Protect your hardwood decks to withstand the sun's harsh ultraviolet rays and heavy foot traffic.

APPLICATION

Deck preparation:

- Remove existing coatings from the wooden surface with Colortone Super Paint Stripper or by sanding
- Using a conventional sander, ensure your wooden deck is properly sanded down
- Wash the deck thoroughly to remove all dust, dirt and oil and allow to dry

Deck Protector application:

- **Stir** the Deck Protector contents **well** before use
- Use a paintbrush or roller to apply Deck Protector
- Apply three undiluted coats of Colortone Deck Protector
- **Pro tip:** Ensure your deck is **sealed all around**
- Clean brush or roller with mineral turpentine
- Approx. drying time is 3-4 days at 25 degrees Celsius (weather dependent)
- Approx. surface coverage is 10-12m² per litre depending on the type of wood

HEALTH & SAFETY

- Flammable
- Keep out of reach of children
- Store in a cool dry area
- Can cause skin and eyes irritation
- Ensure protective gear / PPE is worn

LIABILITY CLAUSE

Colortone Paints CC does not accept liability for any loss or damage incurred from the misapplication of this product, as the application is out of our control.

Colortone Paints CC

P.O. Box 2176, Clareinch, 7740

Tel: +27 21 703 1553

E-mail: info@colortone.co.za

www.colortone.co.za