

## **DATA SHEET: COLORTONE WOOD COAT**

**Product:** WOOD COAT (Exterior & Interior)

**Colours:** Clear, Teak, Mahogany, Dark Oak, and White

**Available sizes:** 1lt, 5lt and 20 litres

**Finish:** Suede finish

**Description:**

Colortone Wood Coat is a water-based, two-in-one, lead-free, easy to apply coating that acts as a durable and rapid drying sealer and a varnish to protect all types of exterior and interior wood from the sun's harsh ultraviolet rays. The two-in-one purpose formulation protects and preserves the natural beauty of your wood surfaces.

### **APPLICATION**

**Wood surface preparation:**

- Remove existing coatings from the wooden surface with Colortone Super Paint Stripper or by sanding
- Wash the surface thoroughly to remove all dust, dirt and oil and allow to dry

**Wood Coat application:**

- **Stir** the Wood Coat contents **well** before use
- Use a paintbrush to apply Wood Coat
- For your first coat of Wood Coat, dilute with 10% water
- Thereafter apply two additional coats of undiluted Wood Coat
- **Pro tip:** Sand surface lightly in between each coat applied for best results
- Clean brush with water
- Approx. drying time under ideal conditions is 2 hours at 25 degrees Celsius (weather dependent)
- Approx. softwood coverage is 8-10m<sup>2</sup> per litre
- Approx. hardwood coverage is 10-12m<sup>2</sup> per litre

### **HEALTH & SAFETY**

- Flammable
- Keep out of reach of children
- Store in a cool dry area
- Can cause skin and eyes irritation
- Ensure protective gear / PPE is worn

### **LIABILITY CLAUSE**

Colortone Paints CC does not accept liability for any loss or damage incurred from the misapplication of this product, as the application is out of our control.

Colortone Paints CC

P.O. Box 2176, Clareinch, 7740

Tel: +27 21 703 1553

E-mail: [info@colortone.co.za](mailto:info@colortone.co.za)

[www.colortone.co.za](http://www.colortone.co.za)