

DATA SHEET: COLORTONE WOOD SEAL

Product: WOOD SEAL (Exterior)

Colours: Clear, Teak, Mahogany, Dark Oak, Meranti

Available sizes: 500ml, 1lt, 2lt, 5lt and 25 litres

Finish: Matt finish

Description:

Colortone Wood Seal is a lead-free, solvent-based, UV protective, water repellent finish for exterior wooden surfaces. Sealing exterior window frames, doors, gates, fences, Wendy-houses, and pergolas.

APPLICATION

Wood surface preparation:

- Remove existing coatings from the wooden surface with Colortone Super Paint Stripper or by sanding
- Wash the surface thoroughly to remove all dust, dirt and oil and allow to dry

Wood Seal application:

- **Stir** the Wood Seal contents **well** before use
- Use a paintbrush to apply Wood Seal
- For your first coat of Wood Seal, dilute 10% with mineral turpentine. Thereafter apply two additional coats of undiluted Wood Seal
- Clean brush with mineral turpentine
- Approx. drying time under ideal conditions is 3 to 4 days at 25 degrees Celsius (weather dependent)
- Approx. surface coverage is 10-12m² per litre depending on the type of wood

HEALTH & SAFETY

- Flammable
- Keep out of reach of children
- Store in a cool dry area
- Can cause skin and eyes irritation
- Ensure protective gear / PPE is worn

LIABILITY CLAUSE

Colortone Paints CC does not accept liability for any loss or damage incurred from the misapplication of this product, as the application is out of our control.

Colortone Paints CC

P.O. Box 2176, Clareinch, 7740

Tel: +27 21 703 1553

E-mail: info@colortone.co.za

www.colortone.co.za