

DATA SHEET: COLORTONE WOOD VARNISH

Product: WOOD VARNISH (Interior & Exterior)

Colours: Clear, Teak, Mahogany, Dark Oak, Meranti, Yellow Wood, Light Oak

Available sizes: 500ml, 1lt, 2lt, 5lt and 25 litres

Finish: Gloss finish

Description:

Colortone Wood Varnish is a solvent-based, lead-free, exterior, and interior, UV protective Wood Varnish for use on all your wooden furniture, ceilings, doors, skirtings, windows etc.

APPLICATION

Wood surface preparation:

- Remove existing coatings from the wooden surface with Colortone Super Paint Stripper or by sanding
- Wash the surface thoroughly to remove all dust, dirt and oil and allow to dry

Wood Varnish application:

- **Stir** the Wood Varnish contents **well** before use
- Using a paintbrush apply the first coat of Wood Varnish, dilute 10% with mineral turpentine

- Thereafter apply two undiluted coats of Wood Varnish
- **Pro tip:** Sand lightly in between each coat applied, for best results
- Clean brush or roller with mineral turpentine
- Approx. drying time is 6 hours at 25 degrees Celsius (weather dependent)
- Approx. surface coverage is 10-12m² per litre depending on the type of wood

HEALTH & SAFETY

- Flammable
- Keep out of reach of children
- Store in a cool dry area
- Can cause skin and eyes irritation
- Ensure protective gear / PPE is worn

LIABILITY CLAUSE

Colortone Paints CC does not accept liability for any loss or damage incurred from the misapplication of this product, as the application is out of our control.

Colortone Paints CC

P.O. Box 2176, Clareinch, 7740

Tel: +27 21 703 1553

E-mail: info@colortone.co.za

www.colortone.co.za