



DATA SHEET

WOODVARNISH SIDE 500ML/1LT/5LT SHEEN FINISH

- Colortone Woodvarnish is a solvent based exterior/interior UV protective woodvarnish
- Colortone Woodvarnish is available in clear,dark oak,mahogany,merranti,teak and yellow wood

HEALTH AND SAFETY

- This product is flammable.
- Store in a cool dry area.
- Keep out of reach of children.
- If contents are ingested,seek urgent medical attention.

WOODVARNISH SIDE

APPLICATION

- Ensure that the entire wooden surface is dry and free of dirt and oil.
- Remove all existing coatings from the wooden surface.
- Remove all dust, wash down wooden surface and allow to dry.
- Apply the first coat by diluting 10% of the quantity of Colortone Woodvarnish can with an equal quantity of mineral turpentine.
- Apply a further two undiluted coats of Colortone Woodvarnish using a brush.
- Under ideal conditions at 25c drying is approximately six hours.
- Product coverage is approximately 10-12 square meters per litre but may vary according to the type of wood.
- Clean brushes with mineral turpentine.

Colortone Paints CC does not accept liability for any loss or damage incurred from the misapplication of their product.

Colortone Paints CC
P.O Box 2176, Clareinch, 7740
Tel : 021 7031553
Fax : 021 7031567
www.colortone.co.za