



# COLORTONE

## DATA SHEET: COLORTONE DECK VARNISH

**Product:** DECK VARNISH (Exterior)

**Colours:** Teak, Mahogany, and Dark Oak

**Available sizes:** 1lt, 5lt and 20 litres

**Finish:** Suede finish

**Description:**

Colortone Deck Varnish is a lead-free, UV protective, rapid drying, water-based, easy to apply exterior wooden deck coating for **softwood**. Protect your wooden decks from the sun's harsh ultraviolet rays, rainwater, and heavy foot traffic.

**\*Pro tip:** For best drying results, apply Deck Varnish in the early morning, or late afternoon hours when the wooden deck surface temperature is cooler.

**\*Not recommended for cracked and weathered softwood.**

### APPLICATION

**Wooden deck preparation:**

- Remove existing coatings from the wooden surface with Colortone Super Paint Stripper or by sanding
- Using a conventional sander, ensure your wooden deck is properly sanded down
- Wash the deck thoroughly to remove all dust, dirt and oil and allow to dry

**Deck Varnish application:**

- **Stir** the Colortone Deck Varnish contents **well** before use
- Use a paintbrush or roller to apply Deck Varnish
- For your first coat of Deck Varnish, dilute with 10% water
- Thereafter applying two undiluted coats of Deck Varnish to ensure the deck is **sealed all around**
- **Pro tip:** For optimal results, we recommend you give your wooden deck a light sanding in between coats
- Clean brush or roller with water
- Approx. drying time is 2 hours at 25 degrees Celsius (weather dependent)
- Approx. surface coverage is 8-10m<sup>2</sup> per litre depending on the type of wood

### HEALTH & SAFETY

- Keep out of reach of children
- Store in a cool dry area
- Can cause skin and eyes irritation
- Ensure protective gear / PPE is worn

### LIABILITY CLAUSE

Colortone Paints CC does not accept liability for any loss or damage incurred from the misapplication of this product, as the application is out of our control.